


Product: [H126T00](#) 

H126T00 - Broadband Coax, H126T, 18 AWG Solid BC, Tri-shield, PVC Jkt



Product Description

Broadband Coax, H126T, 18 AWG Solid Bare Copper Conductor, PE Insulation, Duofoil + 60% Tinned Copper Braid + Foil Shield, PVC Jacket

Technical Specifications

Product Overview

Suitable Applications:	Broadband, Cable Television (CATV), RF drop cable, Over-The-Air (OTA) antennas
------------------------	--

Construction Details

RG Type:	6
----------	---

Conductor

No. of Elements	Size	Stranding	Nom. Diameter	Material
1	18 AWG	Solid	1 mm	BC - Bare Copper

Insulation

Material	Nom. Insulation Diameter
PE - Polyethylene (Foam)	4.57 mm (0.180 in)

Outer Shield

Layer	Outer Shield Type	Material	Coverage
1	Tape	Tri-Laminate (Alum+Poly+Alum)	100%
2	Braid	Tinned Copper (TC)	60%
3	Tape	Bi-Laminate (Alum+Poly)	100%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	6.9 mm

Outer Jacket1 Table Notes:	According to EN 50290-2-20
----------------------------	----------------------------

Electrical Characteristics

Regularity of Impedance:	Min. 40 dB
--------------------------	------------

Return Loss

Frequency	Min. Return Loss
5 - 470 MHz	20 dB
470 - 1000 MHz	18 dB
1000 - 2000 MHz	16 dB
2000 - 3000 MHz	15 dB

Return Loss Table Notes:	In each frequency band, 3 peak values up to 4 dB lower are allowed
--------------------------	--

Attenuation

Frequency	Nom. Attenuation
5 MHz	1.8 dB/100m
50 MHz	4.7 dB/100m
100 MHz	6.5 dB/100m
230 MHz	9.8 dB/100m

400 MHz	13 dB/100m
800 MHz	18.7 dB/100m
862 MHz	19.5 dB/100m
1000 MHz	21.1 dB/100m
1350 MHz	24.9 dB/100m
1750 MHz	28.8 dB/100m
2150 MHz	32.3 dB/100m
2400 MHz	34.4 dB/100m
3000 MHz	39.2 dB/100m

Attenuation Table Notes:	Max. attenuation 10% higher
--------------------------	-----------------------------

Electricals

Max. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
23 Ohm/km (7.0 Ohm/1000ft)	12 Ohm/km (3.7 Ohm/1000ft)	54 pF/m (16 pF/ft)	75 Ohm	82%

Transfer Impedance

Max. Transfer Impedance
Max. 2.5 mOhm/m

Screening

Frequency	Min. Screening Attenuation
30 - 1000 MHz	95 dB
1000 - 2000 MHz	85 dB
2000 - 3000 MHz	75 dB

Screening Class:	A+
------------------	----

Mechanical Characteristics

Temperature

Operating	Installation	Storage
-40°C To +70°C	-5°C To +50°C	-40°C To +70°C

Bend Radius

Stationary Min.
65 mm (2.6 in)

Bulk Cable Weight:	51 kg/km
--------------------	----------

Standards and Compliance

Environmental Suitability:	Indoor - Euroclass Eca
Flammability / Reaction to Fire:	IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
CENELEC Compliance:	EN 50117-1
UK Regulation Compliance:	UKCA Mark

History

Update and Revision:	Revision Number: 0.245 Revision Date: 02-20-2026
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
H126T00.01B100	White	Flat Box	100 m	8719605087621
H126T00.01500	White	Reel	500 m	8719605087614

regulations based on their individual usage of the product.